

SGT-150LW

Standby Power (kVA)	140
Standby Power (kW)	112
Prime Power (kVA)	127,5
Prime Power (kW)	102
Power Factor (cos phi)	0,8

Standby Current (A)	202
Prime Current (A)	184
Nominal Voltage (V)	400/231
Engine Speed (r.p.m)	1500
Phase	3

Engine Specifications

Engine Brand	LISTER PETTER
Engine Model	LP443G6
Standby Power (Kw/hp)	120/132
Engine Speed (r.p.m)	1500
Total Displacement (L)	4,3
Cylinder Arrangement	4 - L
Bore x Stroke (mm x mm)	105 X 124
Compretn Ratio	16:01
Governor Type	Electronic
Aspiration System	Turbocharged AAC
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	24
Oil Capacity (L)	13
Coolant Capacity (L)	31
Fuel Tank Capacity (L)	450
Maximum Exhaust Gas Temperature (°C)	600
Maximum Exhaust Gas Flow (m3/h)	1140
Maximum Back Pressure (kPa)	10
Cooling Air Flow (m3/min)	204
Fuel Consumption at 50 % (L/h)	14,4
Fuel Consumption at 75 % (L/h)	21,3
Fuel Consumption at 100 % (L/h)	28,3
Cylinder Liner Type	Dry Type
Air Filter Type	Dry Type-Replacable
Radiator	Tropical type up to 52 °C

Alternator Specifications

Alternator Brand	WEG
Alternator Model	251AIHD
Frequency (Hz)	50
Nominal Power (kVA)	140
Nominal Voltage (V)	400
Phase	3
Regulated By	AVR
Voltage Regulation	± 0,5 %
Short Circuit Current	315% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	87,5
THD	<3%
Connection Type	Star connection
Number of Wires	12
Poles	4 pole
Bearing Type	Single Bearing




Open Type Dimensions and Weight

Width (mm)	1200
Length (mm)	2400
Height (mm)	1703
Weight (Kg)	1400
Fuel Tank Capacity (L)	450

Starkgen reserves the right to introduce changes to models and features without prior notice

Canopy Type Dimensions and Weight

Width (mm)	1200
Length (mm)	3200
Height (mm)	1953
Weight (Kg)	1900
Fuel Tank Capacity (L)	450



STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office
Hürriyet mah. Yakacık D100 Kuzey Yanyol
No49/1 34876 Kartal - İstanbul, Türkiye
T. +90 216 453 0404

Factory
Hanlı Sakarya Mah. Başak Sk. No 56/1
Arifiye - Sakarya, Türkiye
T. +90 264 295 8300

