

SGT-712PW6

Standby Power (kVA)	700
Standby Power (kW)	560
Prime Power (kVA)	637,5
Prime Power (kW)	510
Power Factor (cos phi)	0,8

Standby Current (A)	1065
Prime Current (A)	970
Nominal Voltage (V)	380/220
Engine Speed (r.p.m)	1800
Phase	3

Engine Specifications

Engine Brand	PERKINS
Engine Model	2806A-E18TAG2
Standby Power (Kw/hp)	623/835,5
Engine Speed (r.p.m)	1800
Total Displacement (L)	18,13
Cylinder Arrangement	6-L
Bore x Stroke (mm x mm)	145 x 183
Compreation Ratio	14,5:1
Governor Type	Electronic
Aspiration System	Turbocharged AAC
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	24
Oil Capacity (L)	62
Coolant Capacity (L)	61
Fuel Tank Capacity (L)	1200
Maximum Exhaust Gas Temperature (°C)	489
Maximum Exhaust Gas Flow (m3/h)	7080
Maximum Back Pressure (kPa)	6,9
Cooling Air Flow (m3/min)	852
Fuel Consumption at 50 % (L/h)	66
Fuel Consumption at 75 % (L/h)	95
Fuel Consumption at 100 % (L/h)	127
Cylinder Liner Type	Wet Type-Replacable
Air Filter Type	Dry Type-Replacable
Radiator	Tropical type up to 50 °C

Alternator Specifications

Alternator Brand	WEG
Alternator Model	315MI20AI
Frequency (Hz)	60
Nominal Power (kVA)	691
Nominal Voltage (V)	380
Phase	3
Regulated By	AVR
Voltage Regulation	± 0,5%
Short Circuit Current	250% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	93,8
THD	<3%
Connection Type	Star connection
Number of Wires	12
Poles	4 pole
Bearing Type	Single Bearing




Open Type Dimensions and Weight

Width (mm)	1900
Length (mm)	3600
Height (mm)	2253
Weight (Kg)	4700
Fuel Tank Capacity (L)	1200

Starkgen reserves the right to introduce changes to models and features without prior notice

Canopy Type Dimensions and Weight

Width (mm)	1900
Length (mm)	5200
Height (mm)	3110
Weight (Kg)	6000
Fuel Tank Capacity (L)	1200



STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office

Hürriyet mah. Yakacık D100 Kuzey Yanyol
No49/1 34876 Kartal - İstanbul, Türkiye
T. +90 216 453 0404

Factory

Hanlı Sakarya Mah. Başak Sk. No 56/1
Arifiye - Sakarya, Türkiye
T. +90 264 295 8300

